



小单目测距望远镜机芯选型表

	参数规格	常规款			小型日韩款		测绘专业款	户外高端款
	机芯名称	J51L0	J51K0-6倍	J51S0	J51N0	J5CC0	J51M0	J51G0
	机芯图片							
物理参数	机芯尺寸	108x63x31.5mm	94.7x63x31mm	86x68x32.7mm	84x43x26 mm	98x40x32.5mm	94x67x28.5mm	94x69x28.5mm
	电池方案	CR2-3V锂电 800mAh内置充电	CR2-3V锂电 800mAh内置充电	CR2-3V锂电池			CR2-3V锂电 18650	CR2-3V锂电
测距参数	最大测程	3000m	1500m	1000m	1000m	1000m	5000m	3000m
	响应时间	0.8s@ < 400m						
	锁旗距离	≤300m						
	测量精度	±1m@<400m;						
	功能选配	测距/测角/测高/测水平距离/两点测高/测速/旗杆锁定/坡度修正/振动;						
	定制功能					空间两点距	空间两点距，方位角，蓝牙，GPS	蓝牙
	测角范围	±60° (±90°可定制)						
	工作温度	-10 ~ +50						
光学参数	放大倍率	6X				7X		
	视场角	6.3°	7°	6.5°	6.3°	6.6mm	6.6mm	6.5mm
	视野范围	110m/1000M	122m/1000M	114m/1000M	110m/1000M	116m/1000M	116m/1000M	114m/1000M
	物镜直径	24mm	24mm	20mm	22mm	24mm	24mm	24mm
	目镜直径	14mm	16mm	13mm	14mm	16mm	16mm	16mm
	出瞳距离	18.2mm	15.5mm	16.7mm	16.7mm	15.5mm	15.5mm	15.5mm
	出瞳直径	3.7mm	4mm	3.33mm	3.3mm	3.4mm	3.3mm	3.4mm
	显示屏类型	低透LCD	低透LCD	低透LCD	低透LCD	高透LCD	低透LCD	反射式OLED屏
					高透LCD	透过式OLED红绿屏	高透LCD	高透LCD
					透过式OLED红绿屏		透过式OLED红绿屏	反射式OLED屏+高透
	低透屏		高透屏		透过式OLED红绿屏		反射式OLED屏	
屏显效果								
屏幕全显				